▶ TASK Inspect, remove, and replace shock absorbers; inspect mounts and bushings.



| Time off |
|----------|
| |
| Time on |
| |
| |
| |
| |

Total time_

CDX Tasksheet Number: C202

- 1. Research the shock absorber removal and installation procedure in the appropriate service information. Follow all directions.
 - a. Shock absorber fastener torque: __ _ ft-lbs/Nm
 - b. List the flat rate time for this job: _____ hrs
- 2. Carefully bounce check the shock absorbers by pushing on each corner of the bumpers. Let go at the bottom of the travel and observe how many oscillations it takes for the vehicle to come to a stop. List your observations:
- 3. Safely raise and support the vehicle on a hoist. Check to see that the vehicle is secure on the hoist, and then remove the shock absorbers following the service information procedures.

NOTE Be sure to support the suspension, or axle assembly, with safety stands before removing the shocks.

- 4. Inspect the shock absorbers, rubber bushings (bushes), and mounts and list your observations:
 - a. Shock absorbers:
 - b. Rubber bushings (bushes):
 - c. Shock mounts:

5. Determine any necessary action(s):

- **6.** Have your supervisor/instructor verify the removal and your observations. Supervisor's/instructor's initials: _
- 7. Reinstall the shock absorbers according to the specified procedure. Be sure to torque all fasteners properly.
- **8.** Have your supervisor/instructor verify satisfactory completion of this procedure, any observations found, and any necessary action(s) recommended.

| Performance Rating | CDX Tasksheet Number: C202 | | |
|---------------------------------|----------------------------|---|------|
| | | | |
| | | | |
| 0 1 | 2 | 3 | 4 |
| Supervisor/instructor signature | | | Date |