

**► TASK** Replace brake lines, hoses, fittings, and supports.

**AST**  
5B7

**MAST**  
5B7

Time off: \_\_\_\_\_

Time on: \_\_\_\_\_

Total time: \_\_\_\_\_

**CDX Tasksheet Number: C623**

1. Safely raise and secure the vehicle on the hoist and, where appropriate, drain the brake line of fluid and safely dispose of it.

**NOTE** You may be able to use a brake pedal depressor to hold down the brake pedal slightly. This will close off the compensating ports in the master cylinder and therefore minimize the amount of fluid draining out of the system. Just remember that the brake lights will stay on continuously while the pedal is depressed.

2. Carefully remove (using flare nut wrenches) any brake lines, hoses, fittings, and supports that are to be replaced.
3. **Have your instructor initial to verify removal:** \_\_\_\_\_
4. Replace any removed flexible hoses, fittings, and supports in accordance with the service manual procedure.

**NOTE** Be sure to properly route the lines and tighten adequately.

5. Fill the master cylinder reservoir with the specified fluid.
6. Bleed the system in accordance with the recommended procedure.
7. **Test the system for leaks and integrity. List your observations:**

8. Have your supervisor/instructor verify satisfactory completion of this procedure, any observations found, and any necessary action(s) recommended.

**Performance Rating**

**CDX Tasksheet Number: C623**

**0**

**1**

**2**

**3**

**4**

Supervisor/instructor signature \_\_\_\_\_ Date \_\_\_\_\_